

Our Docket No.: 37261P090
Express Mail No.: EV339916839US

UTILITY APPLICATION FOR UNITED STATES PATENT
FOR
A LOCK MECHANISM

Inventor(s):
Christodoulos Toulis
Peter Gordon Sclater

BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP
12400 Wilshire Boulevard, Seventh Floor
Los Angeles, California 90025
Telephone: (310) 207-3800

TITLE OF INVENTION**A LOCK MECHANISM****BACKGROUND OF THE INVENTION**

5 This invention relates to a lock mechanism. The lock is primarily intended for a sliding door or window application.

In the following disclosure the door lock according to the invention will be described in the context of a mortice lock.

10 However, it will be apparent to those skilled in the art that the lock mechanism in one or more of its possible forms could also be incorporated in a housing intended for rim or surface mounting. Consequently while the following description will describe a mortice lock any reference to lock housing or lock

15 body should be read in the context of the housing or body being suitable for a mortice lock mounting i.e. within the door or a rim/surface mounting application.

Mortice locks for e.g. sliding doors provide a number of

20 functions such as simple latching and unlatching of the door, so called day latching and deadlocking. To achieve these functions one lever is provided for latching, another lever or the like for day latching and a key cylinder for deadlocking. Visually the lock furniture associated with the

lock takes on a "very busy" appearance resulting from the two levers and key cylinder. This also tends to restrict the size of the levers which can be used, otherwise the levers can be difficult to access and use. Thus, there are issues
5 of appearance and user friendliness associated with existing locks. While these are manifested in the externally visible lock furniture the construction and arrangement of the lock mechanism dictates the number and/or type of external levers, snib etc. and position of the key cylinder.

10

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a lock which requires only a single actuation lever on both
15 interior and exterior sides of a closure with which the lock is associated in order to achieve latching and day latching functions.

Broadly according to one aspect of the invention there is
20 provided a lock mechanism including a lock body, a lock beak rotatably mounted within the lock body and biased by bias means to a first position, the lock beak being co-operable with a hook of a strike as the hook engages in the body whereby the lock beak rotates to a second position against

the bias of the biasing means, and operating members within the lock body operable by external actuating means whereby the operating members can be independently operated to cause the lock beak to move from said first position to said second
5 position and one said operating member to retain the lock beak in said first position.

Preferably the lock further includes means to prevent the other of the operating members from being operable to retain
10 a lock beak in said first position.

According to one form of the invention the lock includes a slide member operable by a lock cylinder to effect a deadlocking function.

15

Preferably the slide member provides a mounting for at least one shoot bolt.

The slide member preferably includes a first engagement means
20 which is engageable with the lock beak to cause deadlocking of the lock beak in the first position. Preferably the slide member includes a second engagement means which is engageable with at least one of the operating members to prevent operation thereof by the external actuating means.

The lock preferably further includes a retention spring means which is engageable with a cam of a lock cylinder to retain the cam when in the position which corresponds to the slide member having been moved by the cam to a deadlocked position.

Preferably the retention spring additionally applies a detent to the slide member when the slide member is in the non-deadlocking position.

10

BRIEF DESCRIPTION OF THE DRAWINGS

In the following more detailed description of the invention reference will be made to the accompanying drawings in which:-

15

Figure 1 is a perspective view of the lock with a cover plate of the lock body/housing removed to show the componentry of the lock mechanism, the lock being shown in the unlatched position but in juxtaposition with a strike,

20

Figure 2 is a view similar to Figure 1 but with the lock mechanism in its initial operation of movement of a locking beak interengaging with the strike,

5 Figure 3 is a perspective view of part of the section of a sliding door with the lock mechanism according to the present invention mortice mounted therein and associated with internal and external latch furniture,

10 Figure 4 is a reverse view of the arrangement shown in Figure 3 but further incorporating the strike,

15 Figure 5 is a further perspective view of the sliding door section with furniture and strike but from a viewpoint different to that of Figure 4.

20 Figure 6 is an inside face view of an item of lock furniture for use with the lock according to the present invention,

Figure 7 is an elevation view of the arrangement shown in Figures 1 and 3 but with the lock mechanism moved to the day latched position where the lock beak has engaged with the strike and the lock beak is engaged by

a sliding foot to prevent the lock beak from being actuated,

5 Figure 8 is a perspective view of the lock mechanism as shown in Figure 7 but with the mechanism having advance further in its latching operation,

10 Figure 9 is a side elevation view of the lock according to the present invention,

Figure 10 is a section on line D-D of Figure 9,

15 Figure 11 is a view similar to Figure 8 but showing the top and bottom shot bolts in the unlocked position,

Figure 12 is a side elevation view with the lock in the configuration shown in Figure 11, and

20 Figure 13 is a cross-section view taken on line B-B of Figure 12.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS OF THE
INVENTION

The lock includes a lock body or housing 10 into which the various components of the locking mechanism (as hereinafter described) are fitted. The housing 10 is closed by a cover which is not shown in the drawings so that the internal
5 workings of the lock can be shown. The housing 10 further includes a front edge faceplate 10a and a rear wall 10b.

In a mortice application the housing 10 is engaged through or in a generally rectangular shape opening formed in the
10 section S of the door. The housing 10 therefore locates within the internal cavity of the door section S with the faceplate 10a fastened to an exterior surface of the side edge of the section S (see Figure 3).

15 The lock is, as normal, associated with furniture components. On the interior side of the door the furniture component comprises a D-handle 14 with a mounting escutcheon 15. Mounted with the escutcheon 15 is a latching lever 16. Extending through an opening in escutcheon 15 is one end of a
20 double lock cylinder L.

On the exterior side of the section S there is provided a pull 17 with associated mounting escutcheon 18. Extending through an opening in escutcheon 18 is the other end of the

lock cylinder L. A latching lever 19 is also mounted with the escutcheon 18.

The lock beak 21 of the lock locates adjacent an opening 22
5 in the faceplate 10a. A hook 20 of strike 13 is engageable through opening 22 as can be seen for example in Figure 1.

The lock beak 21 is pivotally mounted about an axis established by a pair of stub axles 25 which are journaled in
10 suitable bearing areas (not shown) of the housing 10 and cover plate. A sliding foot 23 engages with the lock beak 21 adjacent the hooked end thereof. The sliding foot 23 is biased by a compression spring 24.

15 The lock is therefore self-latching. When the door is moved into the closed position the beak 20 of the strike 13 engages through opening 22 and contacts the lock beak 21. The ramp surface 26 of the strike hook 20 engages with the lock beak 21 causing the lock beak to ride upwardly about the axis of
20 sub-axles 25 and against the action of the spring biased sliding foot 23. Consequently, once the lock beak 21 clears the ramp 26 of the hook strike 20 the spring 24 drives the sliding foot 23 downwardly thereby acting against the hook beak 21 to latch it on to the lock strike 20.

Figure 1 shows the lock beak 21 having cleared the ramp 26 and being acted upon by the sliding foot so that ultimately the sliding foot 23 will ensure that the lock beak 21 engages with the strike hook 20 as shown, for example, in Figure 11.

The lock can be unlatched using both interior and exterior latching levers 16 and 19 respectively. Each of the latching lever 19 has a square drive portion e.g. the drive portion 19a (see Figure 6) which extends into cam 28 which is rotatably mounted within the housing 10. For example, referring to Figure 1 the square drive 19a of exterior lever 19 will engage within square section opening 29 of the cam 28. Likewise the interior latching lever 16 will co-operatively engage with cam 27.

The latching levers 16 and 19 can thus be rotated individually to act on the lock beak 21. This is achieved by an arm 30 or 31 of the respective cams 27 and 28 acting against an abutment portion 32 of the lock beak 21. The action of rotating the latching lever therefore results in the lock beak rising against the sliding foot 23 and out of engagement with the strike 13. Once the strike 13 has moved out of the housing 10 and the latching lever 16 or 19 is

released the lock beak 21 will return to its horizontal or rest position under the action of the sliding foot 23.

The lock can be latched internally by a manual operation of the internal latching lever 16. The external latching lever 19 drives a handing disc 33 (see Figure 2) with its square drive 19a which will not allow the lock to be day latched from the outside.

10 The handing disc 33 is housed in the exterior escutcheon 18. A lug 34 formed on the inside of the escutcheon 18 engages in an arcuate slot 35 in the handing disc 33. The lug 34 abuts one end of the slot 35 thus preventing the latching lever 19 being moved in a direction would be necessary in order to day
15 latch the mechanism. The handling disc thus prevents the lock being placed into the day latched condition from the outside of the door only. This overcomes a problem which could arise if the lock were able to accidentally be day latched as a user exits the door thereby preventing other
20 users from being able to open the door from the inside.

The lock is manually latched when the interior latching lever 16 rotates the female or male cams 27/28 so that the surface 36 at the end of the arm 31 is adjacent or in contact with

surface 37 of the sliding foot 23. The cam 27 or 28 is held in place by the detent spring 38. Because of the juxtaposition of the end 36 of arm 31, as shown in Figure 7, with the surface 37, the sliding foot 23 cannot slide against the bias of the compression spring 24 and thereby release the lock beak 21.

The lock can be deadlocked via the lock cylinder L from both interior and exterior keys. The key activates cam 40 of the lock cylinder L. This cam 40 acts upon a bottom shoot bolt 41 and a top shoot bolt 42 which are joined and act as one. In effect there is a single slide member which forms shoot bolts 41 and 42. The cam 40 therefore "lifts" the shoot bolts 41/42 so that a projection 43 thereof (see Figure 8) engages with a downwardly projecting portion 44 of the lock beak 21. Similarly a projection 45 of the shoot bolt 41/42 engages with hook shaped portions 46 and 47 of the respective cams 27 and 28. This prevents the lock being unlatched via the latching levers 16 and 19.

20

The shoot bolt 41/42 can also be used to activate and deactivate remote locks (not shown) in the door for added security. Alternatively, the top shoot bolt 41 can be

coupled to a rod which projects through the top of the door and into a keep in the top frame member of the door surround.

When cam 40 of the lock cylinder L is rotated, for
5 deadlocking, the cam 40 rides against a cam retention leaf
spring 50 which is mounted with the sidewall 10b of the
housing 10 in the vicinity of an opening in the sidewall 10b.
The cam retention leaf spring 50 over centres the cam 40 and
thus prevents the shoot bolts 41/42 from being manipulated to
10 un-deadbolt the lock.

The cam retention leaf spring 50 also acts as an additional
detent against shoot bolt 41 in cavity 51 for the unlocked
position (see Figure 11) and in cavity 52 for the locked
15 position (see Figure 8). As will be appreciated all of these
functions are thus accomplished with one component namely the
combined shoot bolts 41/42.

Detent springs 38a also provide a detent action with shoot
20 bolt 41.

The lock cannot be lifted off the strike 13. The lock
housing 10 has a ramp surface 53 and associated step 54
(adjacent the opening 22) which can act against the underside

55 and associated step 56 of the strike 20 in the event that an attempt is made to try and lift the lock off the strike. Furthermore, the strike has an abutment surface 57 which engages with an edge of a cover plate 10a at opening 22.

5 These features combine to prevent any vertical lift of the door in an effort to unlatch the lock.

The lock according to the present invention provides an effective yet straightforward lock construction which

10 provides a number of desirable features. These include:-

- An internal lever 16 which has a combined action of both opening and day latching the lock mechanism.
- A spring element 50 which achieves functions which are
- 15 normally achieved by separate components in known lock constructions. The spring 50 provides a deadlocked condition of the slide element (forming the top and bottom shoot bolts 41/42) via interaction of the cylinder cam 40. It also provides a detented bias of
- 20 the slide 41/42 in both the deadlocked and un-deadlocked state.
- The handing disc 33 prevents the external lever 19 from activating the day latch state.

- An anti-lift feature incorporated into the design of the strike 13.

The lock of the present invention thus enables use of a
5 single actuation lever and cylinder on both the interior and
exterior sides of the closure with which the lock is
associated. This provides advantages such as improved visual
appearance of lock furniture and the use of actuation levers
of a size that are easier to use. It is also believed that
10 the lock design will be such that it is more intuitive to use
from a dwellers point of view. From a manufacturers
viewpoint it is believed there will be reduced costs of
manufacture by reducing the number of levers that need to be
manufactured.

15

Other features of the lock will be apparent to those skilled
in the art. Also it will be apparent to those skilled in the
art that the lock mechanism as described herein is open to
modification within the scope of the invention.

20